

# LITCHI 4S MCH SAE 10W/40

4-STROKE AGRICULTURE PERFORMANCE OIL

**DYADE**  
LUBRICANTS

321101501



## 4-STROKE AGRICULTURE PERFORMANCE OIL

This is a semi-synthetic engine oil suitable for off-road equipment: motors, mechanical transmissions, transaxles, hydraulic systems, wet brakes and compressors. This product ensures optimal system cleanliness and prolongs equipment lifetime. This product meets specifications of many manufacturers and is a perfect product for the whole agriculture fleet

## Product information

People buy this product because they need an excellent universal engine oil for agriculture equipment

### CATEGORY

Agriculture Oils

### BASE OIL

Semi-Synthetic

### AVAILABLE PACKAGING

12x1 L

5x4 L

4x5 L

20 L

60 L

205 L

1000 L

## FUEL ECONOMY RATING

## SPECIFICATIONS

ACEA E3	DIN 51524 T3 HVLDP	NH NH 410B
ALLISON C4 (AGRICULTURE APPLIC.)	EATON VICKERS I-280-S EATON VICKERS M-2950-S	NH NH 420A ZF TE-ML 03A
API CG-4	FORD ESN-M2C134 C / D	ZF TE-ML 05K
API GL-4	FORD ESN-M2C159 B / C	ZF TE-ML 06A
API GL-5 (LOW SPEED / HIGH TORQUE)	FORD FNH 82009203 JD J20C	ZF TE-ML 06B ZF TE-ML 06C
API SF / CE	JD J27	ZF TE-ML 07B
CASE MAT 3525	MF M 1144	ZF TE-ML 07D
CASE MAT 3526	MF M 1145	
CATERPILLAR TO-2	NH NH 024C	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,873
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	94
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	14,1
Viscosity Index	ASTM D2270		154
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,4
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	225
Sulphated ash content	ASTM D874	%	

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADE-LUBRICANTS.COM  
WWW.DYADEGLOBAL.COM