

GEAR-PLUS TOP-MP 150

INDUSTRIAL GEAR OILS

321201201

DYADE
LUBRICANTS



GEAR OIL OFFERING PROTECTION AGAINST MICRO PITTING

This range of mineral gear oils is designed for use in all types of gearboxes. It utilizes the latest base oil technology and a specialized additive package to offer exceptional protection against micro-pitting. Additionally, it exhibits superior extreme pressure (EP) properties, excellent anti-oxidant and anti-rust protection, low foaming tendency, and exceptional anti-wear properties. This product is also designed to quickly separate moisture and maintain optimal filterability. This product is suitable for industrial gears that require EP properties and complies with specifications such as AIST 224, DIN 51517 Part 3CLP, Agma 250.04, SEB 181226, and FLENDER Revision 12.

CATEGORY

■ Gear Oils

BENEFITS

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm ³		0.887
Viscosity @ 40 °C, mm ² /s		150
Viscosity @ 100 °C, mm ² /s		14
Viscosity index		95
Flash point C.O.C., °C		210
Pour point, °C		-15
Copper Corrosion	ASTM D130	1a
Rust test A and B	ASTM D665	Pass
FZG A/8.3/90 A/16.6/90	FZG A/8.3/90 A/16.6/90	>12

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM