

GEAR-PLUS EXT-R 1500

INDUSTRIAL GEAR OILS

321201701

DYADE
LUBRICANTS



GEAR FLUIDS WITH EXTREME PRESSURE (EP) CHARACTERISTICS

This product is specifically designed for heavy-duty, high-temperature applications in gearboxes such as those found in large gearboxes, reducing gears, and rolling mills. It is also suitable for lubricating equipment that requires highly viscous oils. With its excellent oxidation and rust protection, it provides maximum protection to steel and brass materials, and it has the ability to quickly separate water in gearboxes where water ingress may occur. These products are suitable for spur gears, helical gears, bevel gears, industrial hypoid gears, worm gears, open gears

CATEGORY

■ Gear Oils

BENEFITS

| PROPERTY | METHOD | VALUE |
|---------------------------------------|-----------|---------|
| Base oil | | Mineral |
| Density kg/dm ³ | | 0.901 |
| Viscosity @ 40 °C, mm ² /s | ASTM D445 | 1500 |
| Viscosity index | | 107 |
| Pour point, °C | ASTM D97 | -12 |
| Flash point, °C | ASTM D611 | >200 |
| Copper corrosion 3h @ 100 °C | ASTM D130 | 1a |
| 4-ball test, welding load, kg | IP 239 | 300 |

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM