

GEAR-PLUS EXT-R 3800

INDUSTRIAL GEAR OILS

321201801



GEAR FLUIDS WITH EXTREME PRESSURE (EP) CHARACTERISTICS

This product is specifically designed for heavy-duty, high-temperature applications in gearboxes such as those found in large gearboxes, reducing gears, and rolling mills. It is also suitable for lubricating equipment that requires highly viscous oils. With its excellent oxidation and rust protection, it provides maximum protection to steel and brass materials, and it has the ability to quickly separate water in gearboxes where water ingress may occur. These products are suitable for spur gears, helical gears, bevel gears, industrial hypoid gears, worm gears, open gears

CATEGORY

Gear Oils

BENEFITS

PROPERTY	METHOD	VALUE
Base oil		Mineral
Density kg/dm ³		0.985
Viscosity @ 40 °C, mm ² /s	ASTM D445	3800
Viscosity index		90
Pour point, °C	ASTM D97	-6
Flash point, °C	ASTM D611	>115
Copper corrosion 3h @ 100 °C	ASTM D130	1a
4-ball test, welding load, kg	IP 239	300

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE