

HYDRAU-PLUS LOW-X 32

HYDRAULIC OILS

321300101



SYNTHETIC HYDRAULIC FLUID FOR EXTREME LOW TEMPERATURE APPLICATIONS

Developed for use in hydraulic systems utilized in the food, beverage, and pharmaceutical processing and packaging equipment that operates at extremely low temperatures, this oil is non-toxic. It is also appropriate for other hydraulic systems where a clean, non-staining hydraulic oil is desired. This lubricant is intended for use in gearboxes, reduction units, drive and conveyor chains. To achieve optimal performance, it is recommended that the gearbox be drained of any previous lubricants prior to application.

CATEGORY

- Hydraulic Fluids

BENEFITS

- Low coefficient of friction provides excellent lubrication and reduces wear
- Fully synthetic oil provides extremely low temperature stability and ensures greatly extended servicing intervals.
- Low foaming reduces residue and scum build-up, which extends maintenance intervals

PROPERTY	METHOD	VALUE
Base fluid		PAO
Appearance	Visual	Clear
Viscosity @ 40 °C, mm ² /s	ASTM D445	32
Viscosity @ 100 °C, mm ² /s	ASTM D445	6.1
Viscosity index	ASTM D2270	138
Temperature range, °C		-60 - 200
Pour point, °C	ASTM D97	-63
Flash point C.O.C, °C	ASTM D92	244

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM