

HYDRAU-PLUS LOW-ASX 32

HYDRAULIC OILS

321300301



LOW TEMPERATURE ASHLESS HYDRAULIC FLUID

Specially recommended for low-temperature applications, this high-performance hydraulic fluid is ideal for hydraulic systems utilized in cold environments, such as offshore, outdoor, and cold stores, due to its high viscosity index. This product is formulated without ash and employs top-quality base stocks and special additives to prevent shear and viscosity loss at elevated temperatures.

CATEGORY

- Hydraulic Fluids

BENEFITS

- Ultra low temperature performance
- Excellent anti wear protection
- Good anti oxidation for a long service life
- Excellent anti rust and anti-corrosion properties
- Superior thermal and hydrolysis stability

PROPERTY	METHOD	VALUE
Base oil type		Mineral
Density @ 15 °C, kg/dm ³	ASTM D1298	0,86
Viscosity @ -20 °C, mm ² /s	ASTM D445	352
FOUT	ASTM D445	129
Viscosity @ 40 °C, mm ² /s	ASTM D445	28-34
Viscosity @ 100 °C, mm ² /s	ASTM D445	9
Viscosity index	ASTM D2270	300
Flash point, °C	ASTM D92	>162
Pour point, °C	ASTM D97	-54

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE