
HYDRAU-PLUS
HLP 22

HYDRAULIC OILS





## MINERAL BASED HIGH PERFORMANCE HYDRAULIC FLUID

This high-performance hydraulic fluid is developed using the latest base oil and additive technology. The incorporation of an ashless additive pack ensures that the product delivers optimal performance and an extended service life. This product is versatile and can be utilized in a wide range of hydraulic applications, including light gear boxes, as well as for general lubrication purposes

PROPERTY	METHOD	VALUE	
Density @ 15 °C, kg/dm³	ASTM D3427	0.861	
Viscosity @ 40 °C, mm²/s	ASTM D1401	22	
Viscosity @ 100 °C, mm²/s	ASTM D3427	4.6	
Viscosity index	ASTM D1401	102	
Flash point C.O.C, °C	ASTM D3427	180	
Pour point, °C	ASTM D1401	-36	
Air Release Value @ 50°C	ASTM D3427	Pass	
Demulsibility @ 54 °C	ASTM D1401	Pass	



Hydraulic Fluids

## BENEFITS

- Excellent anti wear protection
- Good emulsifying and air-release properties
- Good anti oxidation for a long service life

DYAD

LUBRICANTS

Excellent anti corrosion properties





## 

## DYADE MAINTAIN THE THINGS WE VALUE