

HYDRAU-PLUS HLP 68

HYDRAULIC OILS

321301001



MINERAL BASED HIGH PERFORMANCE HYDRAULIC FLUID

This high-performance hydraulic fluid is developed using the latest base oil and additive technology. The incorporation of an ashless additive pack ensures that the product delivers optimal performance and an extended service life. This product is versatile and can be utilized in a wide range of hydraulic applications, including light gear boxes, as well as for general lubrication purposes

CATEGORY

- Hydraulic Fluids

BENEFITS

- Excellent anti wear protection
- Good emulsifying and air-release properties
- Good anti oxidation for a long service life
- Excellent anti corrosion properties

PROPERTY	METHOD	VALUE
Density @ 15 °C, kg/dm ³	ASTM D4052	0.882
Viscosity @ 40 °C, mm ² /s	ASTM D445	68
Viscosity @ 100 °C, mm ² /s	ASTM D445	8.7
Viscosity index	ASTM D2270	99
Flash point C.O.C, °C	ASTM D92	180
Pour point, °C	ASTM D97	-27
Air Release Value @ 50°C	ASTM D3427	Pass
Demulsibility @ 54 °C	ASTM D1401	Pass

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE