

# HYDRAU-PLUS FR WG 2

HYDRAULIC OILS

321302001



## FIRE RESISTANT HYDRAULIC FLUID

This is a water-based solution that contains special glycols and an additive package comprising anti-wear, antioxidant, and anticorrosive agents. The fluid meets the ISO HFC class and is suitable for a broad range of hydraulic applications.

## CATEGORY

- Hydraulic Fluids

## BENEFITS

- Outstanding fire resistance thanks to its high water content (>40%)
- Excellent mechanical properties, protects the hydraulic pump against wear
- High anticorrosive and antioxidant characteristic, thanks to the high alkaline reserve
- Prevents the formation of oxidation
- Very shear stable
- Very high viscosity index: minimum viscosity – temperature changes
- Compatible with normally used joints
- Low foaming tendency

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm <sup>3</sup>		1.06
Viscosity @ 40 °C, mm <sup>2</sup> /s		2
Viscosity index		
Pour point, °C		<-40
pH		10

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE