

HYDRAU-PLUS FR WG 68

HYDRAULIC OILS

321302301



FIRE RESISTANT HYDRAULIC FLUID

This is a water-based solution that contains special glycols and an additive package comprising anti-wear, antioxidant, and anticorrosive agents. The fluid meets the ISO HFC class and is suitable for a broad range of hydraulic applications.

CATEGORY

- Hydraulic Fluids

BENEFITS

- Outstanding fire resistance thanks to its high water content (>40%)
- Excellent mechanical properties, protects the hydraulic pump against wear
- High anticorrosive and antioxidant characteristic, thanks to the high alkaline reserve
- Prevents the formation of oxidation
- Very shear stable
- Very high viscosity index: minimum viscosity – temperature changes
- Compatible with normally used joints
- Low foaming tendency

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm ³		1.07
Viscosity @ 40 °C, mm ² /s		68
Viscosity index		>250
Pour point, °C		<-30
pH		10

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE