

HYDRAU-PLUS HVLP ZF 68

HYDRAULIC OILS

321304501



HVI ZINC FREE MINERAL HYDRAULIC FLUID

This product is a high-grade EP oil formulated with a special EP-additive technology, making it a universal HVI Zinc Free mineral oil. This product is designed for use in heavy-duty hydraulic systems as well as light-duty gearboxes, bearings, and general lubrication. However, it should not be used in turbine applications.

CATEGORY

- Hydraulic Fluids

BENEFITS

- Excellent stability against oxidation.
- High Viscosity Index
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.
- Very good thermal stability.
- Avoid reactions with metals like Silver

PROPERTY	METHOD	VALUE
ISO Viscosity Grade		68
Density @ 15 °C, kg/dm ³		0.879
Kinematic Viscosity @ 100 °C, mm ² /s		11.7
Viscosity index		153
Flash point C.O.C, °C		>225
Pour point, °C		-36
FZG Fail Load Stage		>11
Air Release Value @ 50 °C, min		Pass
Demulsibility @ 54°C, min		Pass

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE