

# SLIDE-PLUS WL 68

SLIDEWAY OILS

321400301



## SLIDE OR GUIDE WAY LUBRICANT

The lubricating oils that are designed for use on slides and ways are compounded in a special manner to prevent stick-slip phenomenon during machine tool operation. These products are formulated using a combination of unique base oils, additives, and compounding techniques that provide remarkable stability, exceptional load-bearing capacity, high oiliness, and strong adhesiveness. SLIDE-PLUS WL 68 is ideal for horizontal applications on way guides and slide ways, while SLIDE-PLUS WL 220 is better suited for vertical use and can handle heavier loads. On the other hand, SLIDE-PLUS WL 150 has superior tackiness and can be used for both horizontal and vertical ways, as well as in machines with centralized ways and hydraulic systems.

## CATEGORY

- Industry Specific

## BENEFITS

- Excellent metal wetting properties
- Non corrosive to both metal and non-metal materials
- Exceptional load carrying capabilities
- Eliminates stick slip
- Provides excellent demulsibility characteristics in the present of water based cutting fluids
- No adverse reaction to resin coated surfaces
- Very good corrosion protection

PROPERTY	METHOD	VALUE
Density @ 25 °C, kg/dm <sup>3</sup>		0.88
Viscosity @ 40 °C, mm <sup>2</sup> /s		68
Viscosity index		>90
Flash point, °C		>200
Pour point, °C		<-10
Cu corrosion		1a

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM