

COMP-PLUS ASH-L 32

COMPRESSOR OILS

321500101

DYADE
LUBRICANTS



ASHLESS COMPRESSOR OIL

This product is made up of paraffinic base oils that are highly stable against oxidation and do not contain any ash. It also contains carefully selected additives. The low level of carbon residue in the product prevents the formation of deposits. Its unique formulation provides excellent performance even under harsh conditions. Additionally, it is compatible with elastomers and paint, has a low filter blockage, and exhibits good thermal stability. This product can be used for lubricating screw, rotary, and reciprocating air compressors, as well as vacuum pumps. Additionally, it is suitable for use as an ashless hydraulic oil.

CATEGORY

- Compressor- and Vacuum pump Fluids

BENEFITS

- Excellent filterability resulting in low filter blockage
- Long life
- Low carbon and deposit build up

PROPERTY	METHOD	VALUE
ISO Viscosity Grade	ASTM D2422	32
Viscosity index	ASTM D2270	103
Viscosity @ 40 °C, mm ² /s	ASTM D445	31,9
Viscosity @ 100 °C, mm ² /s	ASTM D445	5,4
Flash point, °C	ASTM D92	>210
Pour point, °C	ASTM D97	<-33
Copper corrosion 24h @ 100 °C	ASTM D130	1a
Demulsibility @ 54 °C	ASTM D1401	40/40/0
Density @ 15 °C, kg/dm ³	ASTM D1298	0.869

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM