
COMP-PLUS SYNT 50

321502901 COMPRESSOR OILS



DDODEDTV

SUPER PREMIUM SYNTHETIC COMPRESSOR FLUID

These environmentally neutral fluids are 100% synthetic and biodegradable. They offer superior oxidation and thermal stability, longer fluid life, and are compatible with OEM polyglycols without the need for compressor flushing. This makes it possible to top up compressors containing polyglycol fluids until the scheduled change intervals. This specialized product is designed for screw compressor applications that demand exceptional cleanliness, extended drain intervals, and superior wear protection. It is also fully compatible with OEM polyglycols, such as Ingersoll Rand SSR Ultracoolant, ensuring seamless integration with existing systems.

VALUE

PRUPERTY	METHOD	VALUE	
ISO Viscosity Grade	ASTM D2422		
Viscosity @ 40 °C, mm²/s	ASTM D445	50.1	
Viscosity @ 100 °C, mm²/s	ASTM D445	9.0	
Viscosity index	ASTM D2270	170	
Flash point, °C	ASTM D92	250	
Pour point, °C	ASTM D97	-49	
Demulsibility @ 130°C, ml	ASTM D1401	40/39/1	
Density @ 15 °C, kg/dm³	ASTM D1298	0.98	
Rust Test	ASTM D6557	Pass	
FZG Gear Test, Pass	ASTM D5182	12	

METHOD



CATEGORY

Compressor- and Vacuumpump Fluids

BENEFITS

- Outstanding oxidation stability
- High flash & auto-ignition points
- Excellent coolant properties
- Very long-life fluid
- Excellent materials compatibility
- Excellent rust & corrosion control
- Very good separation from water



