

VACUUM PLUS MO 150

VACUUM PUMP OILS

321700601

DYADE
LUBRICANTS



MINERAL OIL BASED VACUUM PUMP FLUID

This specialized vacuum pump fluid is designed exclusively for use in vacuum pumps that operate mechanically. This lubricant is suitable for cooling and lubricating vacuum pumps that handle air requiring this specific ISO viscosity grade. It is compatible with standard seal and hose materials. However, it is not recommended for use in pumps that handle strong oxidizing or reactive vapors.

CATEGORY

- Compressor- and Vacuum pump Fluids

BENEFITS

- Excellent protection against corrosion
- Excellent lubricity
- Oxidation stable

PROPERTY	METHOD	VALUE
ISO Viscosity Grade	ASTM D2422	150
Density @ 20 °C, kg/dm ³	ASTM D1298	0.89
Kinematic viscosity @ 40 °C, cSt	ASTM D445	148
Kinematic viscosity @ 100 °C, cSt	ASTM D445	14.3
Viscosity index	ASTM D2270	96
Flash point C.O.C, °C	ASTM D92	245
Pour point, °C	ASTM D97	-21
Vapour pressure @ 20 °C, Pa	ASTM D972	<0.5
TAN, mg KOH/g	ASTM D664	0.2

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM