

# VACUUM-PLUS

## FSV 32

VACUUM PUMP OILS

321702401

**DYADE**  
LUBRICANTS



### FULLY SYNTHETIC VACUUM PUMP FLUID

These premium synthetic vacuum pump fluids are formulated with PAO base oil and designed to provide excellent performance and long fluid life in all types of vacuum pumps. This product is formulated to offer superior protection against wear, rust and corrosion, and is highly effective in providing exceptional service in various types of vacuum pumps, including rotary screw, sliding vane, reciprocating, and liquid ring pumps.

### CATEGORY

- Compressor- and Vacuum pump Fluids

### BENEFITS

- Excellent thermal and chemical stability
- Good oxidative stability
- Excellent wear, rust and corrosion control
- Very high flash point
- Low volatility
- Excellent film strength
- Reduced maintenance costs and downtime

PROPERTY	METHOD	VALUE
ISO Viscosity Grade	ASTM D2422	32
Viscosity @ 40 °C, mm <sup>2</sup> /s	ASTM D445	33.1
Viscosity @ 100 °C, mm <sup>2</sup> /s	ASTM D445	5.9
Viscosity index	ASTM D2270	123
Flash point, °C	ASTM D92	240
Pour point, °C	ASTM D97	-45
Copper corrosion 24h @ 100 °C	ASTM D130	1a
Demulsibility @ 54 °C	ASTM D1401	excellent
Density @ 15 °C, kg/dm <sup>3</sup>	ASTM D1298	0.85

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM