

VACUUM-PLUS

FSV 68

VACUUM PUMP OILS

321702601

DYADE
LUBRICANTS



FULLY SYNTHETIC VACUUM PUMP FLUID

These premium synthetic vacuum pump fluids are formulated with PAO base oil and designed to provide excellent performance and long fluid life in all types of vacuum pumps. This product is formulated to offer superior protection against wear, rust and corrosion, and is highly effective in providing exceptional service in various types of vacuum pumps, including rotary screw, sliding vane, reciprocating, and liquid ring pumps.

CATEGORY

- Compressor- and Vacuum pump Fluids

BENEFITS

- Excellent thermal and chemical stability
- Good oxidative stability
- Excellent wear, rust and corrosion control
- Very high flash point
- Low volatility
- Excellent film strength
- Reduced maintenance costs and downtime

PROPERTY	METHOD	VALUE
ISO Viscosity Grade	ASTM D2422	68
Viscosity @ 40 °C, mm ² /s	ASTM D445	68.3
Viscosity @ 100 °C, mm ² /s	ASTM D445	10
Viscosity index	ASTM D2270	130
Flash point, °C	ASTM D92	250
Pour point, °C	ASTM D97	-43
Copper corrosion 24h @ 100 °C	ASTM D130	1a
Demulsibility @ 54 °C	ASTM D1401	Excellent
Density @ 15 °C, kg/dm ³	ASTM D1298	0.87

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM