

# CHAIN-PLUS HTC 100

CHAIN OILS

321800101

**DYADE**  
LUBRICANTS



## CHAIN OIL FOR LUBRICATION UP TO 150 °C

The product exhibits excellent resistance to aging and adhesion, along with good anti-splash and anti-drip properties. It also demonstrates exceptional high-temperature performance of up to 150 °C. In addition, it reduces noise and provides higher performance compared to traditional lubricants. This product is versatile and can be applied to various types of equipment such as roller chains, conveyor chains, jointed chains, open gears, toothed wheels, toothed couplings, low-speed bearings, and plain bearings. It is highly recommended for use in industries such as textiles, paper, wood, beverages, and metals, as well as in rolling mills, steam power plants, and mines due to its excellent high-temperature characteristics and noise reduction properties.

## CATEGORY

- Chain Lubricants

## BENEFITS

- Increasing chain life
- Reduces maintenance costs
- Lowers power consumption
- Will not splash or drip
- Available in a wide range of viscosities

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm <sup>3</sup>		0.886
Kinematic viscosity @ 40 °C, cSt		100
Viscosity index		>95
Flash point C.O.C, °C		225
Pour point, °C		-10
4-ball wear test, welding load, kg		>180
Aniline point, °C		100
Copper corrosion 3h @ 100 °C		1a
TAN, mg KOH/g		0.6

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM