

# CHAIN-PLUS HTC 320

CHAIN OILS

321800301

**DYADE**  
LUBRICANTS



## CHAIN OIL FOR LUBRICATION UP TO 150 °C

This product boasts high resistance to aging and adhesion, as well as effective anti-splash and anti-drip properties. Its outstanding high-temperature performance, which can reach up to 150°C, sets it apart from conventional lubricants. Additionally, it can reduce noise and significantly enhance performance. This versatile product is applicable to a wide range of machinery, including roller chains, conveyor chains, jointed chains, open gears, toothed wheels, toothed couplings, low speed bearings, and low speed plain bearings. It is especially well-suited for use in industries such as textiles, paper, wood, beverages, and metals, as well as in rolling mills, steam power plants, and mines.

## CATEGORY

- Chain Lubricants

## BENEFITS

- Increasing chain life
- Reduces maintenance costs
- Lowers power consumption
- Will not splash or drip
- Available in a wide range of viscosities

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm <sup>3</sup>		0.894
Kinematic viscosity @ 40 °C, cSt		320
Viscosity index		>95
Flash point C.O.C, °C		230
Pour point, °C		-10
4-ball wear test, welding load, kg		>180
Aniline point, °C		100
Copper corrosion 3h @ 100 °C		1a
TAN, mg KOH/g		0.6

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM