

CHAIN-PLUS AWR 150

CHAIN OILS

321800601

DYADE
LUBRICANTS



ADHERENT, WATER REPELLENT CHAIN OIL

This highly adherent product exhibits exceptional resistance to high pressure and is particularly well-suited for use as a water-resistant agent and lubricant on drive chains and overhead conveyor chains. The fluids do not splash or drip, ensuring superior lubrication compared to traditional lubricants. This product is suitable for use at service temperatures ranging from -20°C up to 150°C. Its outstanding anti-corrosion properties make it particularly well-suited for use in marine and other corrosive environments. It is a versatile oil that can be used on a wide range of equipment, including hoist chains, forklift trucks, chain saws, general machinery, delicate moving parts of robots, and wherever a high-quality light grade oil is required. For optimal performance, apply the product to surfaces that are clean and dry.

CATEGORY

- Chain Lubricants

BENEFITS

- Non-drip properties will extend the lubrication intervals and ensure a clean working area
- Excellent penetration properties provide protection of the moving chain pins and bushes
- Excellent corrosion resistance and dewatering properties allow application to wet or recently washed chains
- The EP additive provides a high degree of wear protection and extends chain life

PROPERTY	METHOD	VALUE
Appearance		Clear fluid, oily liquid
Viscosity @ 40 °C, mm ² /s		150
Viscosity index		>95
Flash point C.O.C, °C		>200
Pour point, °C		<-10
Copper corrosion 3h @ 100 °C		1a

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM