

# CHAIN-PLUS HTC 1000

CHAIN OILS

321802201

**DYADE**  
LUBRICANTS



## TACKY CHAIN OIL FOR LUBRICATION UP TO 150 °C

This product delivers exceptional stability against aging and adhesion, while also exhibiting effective anti-splash and anti-drip properties. It boasts excellent high-temperature performance of up to 150°C, surpassing that of conventional lubricants. Moreover, it reduces noise levels and significantly improves overall performance. This product is versatile and can be applied to various types of machinery, such as roller chains, conveyor chains, jointed chains, open gears, toothed wheels, toothed couplings, low speed operated bearings, and low speed plain bearings. It is particularly well-suited for use in the textile, paper, wood, beverage, and metal industries, as well as in rolling mills, steam power plants, and mines.

## CATEGORY

- Chain Lubricants

## BENEFITS

- Increasing chain life
- Reduces maintenance costs
- Lowers power consumption
- Will not splash or drip
- Available in a wide range of viscosities

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm <sup>3</sup>		0.900
Kinematic viscosity @ 40 °C, cSt		1000
Viscosity index		>110
Flash point C.O.C, °C		>240
Pour point, °C		-5
4-ball wear test, welding load, kg		>180
Aniline point, °C		100
Copper corrosion 3h @ 100 °C		1a
TAN, mg KOH/g		0.6

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM