

# CHAIN-PLUS HTC 4200

CHAIN OILS

321802301

**DYADE**  
LUBRICANTS



## TACKY CHAIN OIL FOR LUBRICATION UP TO 150 °C

This product delivers superior stability against aging and adhesion, while also providing effective anti-splash and anti-drip capabilities. It boasts exceptional high-temperature performance of up to 150°C, surpassing that of traditional lubricants. Additionally, it reduces noise levels and significantly enhances overall performance. This versatile product is applicable to a wide range of machinery, including roller chains, conveyor chains, jointed chains, open gears, toothed wheels, toothed couplings, low-speed operated bearings, and low-speed plain bearings. It is highly suitable for use in various industries such as textiles, paper, wood, beverages, and metals, as well as in rolling mills, steam power plants, and mines.

## CATEGORY

- Chain Lubricants

## BENEFITS

- Increasing chain life
- Reduces maintenance costs
- Lowers power consumption
- Will not splash or drip
- Available in a wide range of viscosities

| PROPERTY                            | METHOD | VALUE |
|-------------------------------------|--------|-------|
| Density @ 20 °C, kg/dm <sup>3</sup> |        | 0.915 |
| Kinematic viscosity @ 40 °C, cSt    |        | 4200  |
| Viscosity index                     |        | 120   |
| Flash point C.O.C, °C               |        | 260   |
| Pour point, °C                      |        | -6    |
| 4-ball wear test, welding load, kg  |        | >200  |
| Aniline point, °C                   |        | 105   |
| Copper corrosion 3h @ 100 °C        |        | 1a    |
| TAN, mg KOH/g                       |        | 0.6   |

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM