

# CLEAN-PLUS TOP PAG

CLEANERS

322101601

**DYADE**  
LUBRICANTS



## CIRCUIT CLEANER

This product is specifically designed for cleaning circuits, pipes, and sumps and contains a synthetic fluid that effectively removes varnish and sludge. The cleaning action of this fluid is based on its solvency, which is derived from esters and PAG, making it suitable for cleaning only circuits with PAG. It should not be used with mineral or PAO oils as it is not compatible with them. The following are the instructions for using this fluid: Mix 10% of the fluid with the fluid currently in use. Leave the mixture in the system for 12 to 48 hours, while keeping the oil in circulation and allowing it to reach the operating temperature. After this period, drain the system, clean the filters, and refill with fresh oil.

## CATEGORY

- Cleaners

## BENEFITS

- Removes oil and sludge deposits
- High flash point compared and low toxicity
- Cleans and degreases filters, acid compounds, sludges and varnishes
- Exceptional solvent power
- Help to extend service life of compressor

PROPERTY	METHOD	VALUE
Colour		Yellowish
Density kg/dm <sup>3</sup>		0.98
Kinematic viscosity @ 40 °C, cSt		45
Kinematic viscosity @ 100 °C, cSt		7
Viscosity index		120
Flash point, °C		240
Pour point, °C		-45

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM