

COOL-PLUS POE GEN 32

REFRIGERATION OILS

322202101

DYADE
LUBRICANTS



ADVANCED HFC REFRIGERATION COMPRESSOR FLUID

This high-performance lubricant is a blend of polyolester (POE) refrigeration lubricants and ashless additives, designed to provide superior protection for HFC refrigeration systems. It offers excellent solubility and lubricity in HFC and blended refrigerants, with exceptional chemical and thermal stability for a long service life.

CATEGORY

Refrigeration Fluids

BENEFITS

| PROPERTY | METHOD | VALUE |
|-------------------------------------|-----------|----------------|
| Appearance | | Bright & clear |
| Base oil type | | Polyol ester |
| Color APHA | MD 31 | <200 |
| Density @ 15 °C, kg/dm ³ | ISO 12185 | 0.950 |
| Acid number, mg KOH/g | ISO 6618 | <0.1 |
| Kin. viscosity 40 °C, cSt | ISO 3104 | 32 |
| Viscosity index | ISO 2909 | 149 |
| Water content, ppm | MO-10-001 | <50 |
| Pour point, °C | ISO 3016 | <-50 |
| Flash point C.O.C, °C | ISO 2592 | >230 |

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM