

COOL-PLUS POE GEN 55

REFRIGERATION OILS

322202401

DYADE
LUBRICANTS



ADVANCED HFC REFRIGERATION COMPRESSOR FLUID

This high-performance lubricant is a blend of polyolester (POE) refrigeration lubricants and ashless additives, designed to provide superior protection for HFC refrigeration systems. It offers excellent solubility and lubricity in HFC and blended refrigerants, with exceptional chemical and thermal stability for a long service life.

CATEGORY

Refrigeration Fluids

BENEFITS

PROPERTY	METHOD	VALUE
Appearance		Bright & clear
Base oil type		Polyol ester
FOUT	MD 31	<200
Density @ 15 °C, kg/dm ³	ISO 12185	0.951
Acid number, mg KOH/g	ISO 6618	<0.1
Kin. viscosity 40 °C, cSt	ISO 3104	55
Viscosity index	ISO 2909	145
Water content, ppm	MO-10-001	<50
Pour point, °C	ISO 3016	<-43
Flash point C.O.C, °C	ISO 2592	>234

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM