

COOL-PLUS POE GEN 80

REFRIGERATION OILS

322202601



ADVANCED HFC REFRIGERATION COMPRESSOR FLUID

This high-performance lubricant is a blend of polyolester (POE) refrigeration lubricants and ashless additives, designed to provide superior protection for HFC refrigeration systems. It offers excellent solubility and lubricity in HFC and blended refrigerants, with exceptional chemical and thermal stability for a long service life.

CATEGORY

Refrigeration Fluids

BENEFITS

PROPERTY	METHOD	VALUE
Appearance		Bright & clear
Base oil type		Polyol ester
Color APHA	MD 31	<200
Density @ 15 °C, kg/dm ³	ISO 12185	0.952
Acid number, mg KOH/g	ISO 6618	<0.1
Kin. viscosity 40 °C, cSt	ISO 3104	80
Viscosity index	ISO 2909	144
Water content, ppm	MO-10-001	<50
Pour point, °C	ISO 3016	<-40
Flash point C.O.C, °C	ISO 2592	>240

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM