

# COOL-PLUS POE GEN 320

REFRIGERATION OILS

322203201

**DYADE**  
LUBRICANTS



#### ADVANCED HFC REFRIGERATION COMPRESSOR FLUID

This high-performance lubricant is a blend of polyolester (POE) refrigeration lubricants and ashless additives, designed to provide superior protection for HFC refrigeration systems. It offers excellent solubility and lubricity in HFC and blended refrigerants, with exceptional chemical and thermal stability for a long service life.

#### CATEGORY

Refrigeration Fluids

#### BENEFITS

PROPERTY	METHOD	VALUE
Appearance		Bright & clear
Base oil type		Polyol ester
FOUT	MD 31	<200
Density @ 15 °C, kg/dm <sup>3</sup>	ISO 12185	0.970
Acid number, mg KOH/g	ISO 6618	<0.05
Kin. viscosity 40 °C, cSt	ISO 3104	300
Viscosity index	ISO 2909	92
Water content, ppm	MO-10-001	<50
Pour point, °C	ISO 3016	-24
Flash point C.O.C, °C	ISO 2592	280

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM