
COOL-PLUS POE HYB 100

REFRIGERATION OILS 322203301



AUTOMOTIVE A/C LUBRICANT FOR HYBRID VEHICLES

This advanced lubricant is tailored for automotive air conditioning in hybrid gasoline electric vehicles. Its high electrical resistance is a crucial feature for hybrid a/c systems. The product has been specially formulated to offer exceptional solubility and superior lubricity for R-I34a automotive a/c systems.

PROPERTY	METHOD	VALUE	
Viscosity @ 40 °C, mm²/s	ISO 3104	91	
Viscosity @ 100 °C, mm ² /s	ISO 3104	12.6	
Viscosity index	ISO 2909	135	
Pour point, °C	ISO 3016	-37	
Flash point C.O.C, °C	ISO 2592	271	
Copper corrosion 24h @ 100 °C	ASTM D4048	la	



CATEGORY

Refrigeration Fluids

BENEFITS

- Excellent solubility R-134A HFC refrigeration systems
- High dielectric strength (excellent electrical resistance)
- Very high viscosity index for better compressor protection at elevated temperatures
- Excellent low temperature fluidity
- Very high flash & auto-ignition points for added safety
- Very long life fluid allows for extended oil drains
- Excellent film strength and anti wear properties
- Excellent carbon and varnish control to help reduce deposits
- Excellent rust control



