

# COOL-PLUS PAG GEN 100

REFRIGERATION OILS

322203601

**DYADE**  
LUBRICANTS



## PREMIUM POLYALKYLENE GLYCOL REFRIGERATION LUBRICANT

Specifically designed for automotive air conditioning applications, these lubricants are premium refrigeration lubricants made from double end capped polyalkylene glycol. They are manufactured to meet OEM requirements using advanced technology additive systems that provide superior protection for 134a HFC and R1234yf HFO refrigeration systems. These lubricants offer exceptional solubility and superior lubricity in automotive HFC and HFO refrigerants. This is a lubricant that is utilized in compressors for HFC and HFO refrigeration systems.

## CATEGORY

- Refrigeration Fluids

## BENEFITS

- Excellent oxidation stability
- Long fluid life
- Very high flash & auto-ignition points
- High film strength
- Excellent coolant properties
- Unsurpassed solubility in HFC and HFO and blended refrigerants
- Excellent rust control
- Carbon and varnish control

## PROPERTY

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm <sup>3</sup>	ASTM D1298	0.989
FOUT	ASTM D445	95
FOUT	ASTM D445	16.19
Viscosity index		183
Pour point, °C	ASTM D97	-47
Flash point, °C	ASTM D92	232
Copper corrosion	ASTM D130	1a
Auto ignition point, °C	ASTM D97	391

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM