

ATF STOP LEAK

STOPS AND PREVENTS LEAKAGE IN ATF AND POWER STEERING

322900201

DYADE
LUBRICANTS



AUTOMATIC TRANSMISSION STOP LEAK

This ATF Stop Leak is developed in order to rejuvenate the rubber seals and O rings. It stops and prevents leakage and protects the system. The result is easy shifting and it prevents the automatic transmission fluid from ageing.

Product information

“People buy this product because they want to stop the leak in their Automatic Transmission”

CATEGORY

Car additive ATF Stop Leak

MAIN BENEFITS

- Ensures easy shifting
- Increases ATF lifetime
- Stops leakage of ATF fluids

AVAILABLE PACKAGING

300 ML

HOW TO USE?

This product can be used in all conventional ATF fluids that meet the Dexron II, III, Vi, Ford, LHM or other equivalent specifications. It is also particularly suitable for Power Steering Systems that have an Automatic Transmission Fluid.

PRODUCT SPECIFICATIONS ATF STOP LEAK

TEST	UNIT	VALUE
Appearance		Brown
Density @ 20 °C	kg/l	0.877
Kinematic viscosity @ 40 °C	mm ² /s	1.480
Kinematic viscosity @ 100 °C	mm ² /s	5.4

All data on this technical data sheet is indicative only

201902V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM