


FOODGRADE CHAIN OILS



323200801

FOOD GRADE OIL FOR THE LUBRICATION OF DRIVE AND CONVEYOR CHAINS IN LOW TEMPERATURE **APPLICATIONS**

Formulated with a combination of synthetic hydrocarbons, this product is designed to provide a long-wet film life over a wide temperature range by being inhibited against oxidation. Its primary purpose is to lubricate conveyor chains and bearings that operate continuously at low temperatures, reaching as low as -40°C. It is especially suited for slow-moving chains.To use on drive and conveyor chains, apply the product sparingly with a brush or oil can as needed. Alternatively, it can be applied automatically through a central drip feed system.

PROPERTY	METHOD	VALUE	
Colour		0.5	
Density @ 20 °C, kg/dm³		0.82	
Viscosity @ 40 °C, mm²/s		17	
Viscosity @ 40 °C, mm²/s		2500	
Viscosity index		125	
TAN, mg KOH/g		<]	
Flash point, °C		>220	
Pour point, °C		<-60	
NSF registration		151578	
Kosher approved		yes	
Halal approved		yes	



CATEGORY

Chain Lubricants

BENEFITS

- Penetrates to the links and pins reducing wear and extending chain life
- Does not form hard carbon deposits
- Miscible with esters, mineral oils and other synthetic hydrocarbons
- Avoids high speed splashing and therefore staining of fabrics
- Excellent anti-wear properties
- Low volatility that reduces the evaporation residues

All data on this technical data sheet is indicative only



TYPOGRAAF 16 | 6921 VB DUIVEN

DYADE MAINTAIN THE THINGS WE VALUE