FOOD-PLUS ECO COMP 32

FOODGRADE & BIODEGRADABLE COMPRESSOR OILS

323301301



SYNTHETIC BIODEGRADABLE COMPRESSOR AND **VACUUM PUMP LUBRICANT - FOOD GRADE**

The combination of top-quality synthetic base fluids and carefully crafted additive systems makes this product highly effective in machinery that operates under severe conditions and requires a food grade and/ or eco-friendly lubricant at this ISO viscosity grade. Furthermore, the product is specifically designed for use in the food and beverage industries where incidental contact with lubricants may occur.

PROPERTY	METHOD	VALUE	
ISO Viscosity Grade	ASTM D2422	32	
Viscosity @ 100 °C, mm²/s	ASTM D445	6.3	
Viscosity @ 40 °C, mm²/s	ASTM D445	33	
Viscosity index	ASTM D2270	141	
Pour point, °C	ASTM D97	-45	
Flash point C.O.C, °C	ASTM D92	255	
Density @ 15 °C, kg/dm³	ASTM D1298	0.96	



CATEGORY

Compressor- and Vacuumpump Fluids

BENEFITS

- Low toxicity
- Ready biodegradable (OECD 301B) and virtually non-toxic. These products are an excellent choice where leakage or spillage could enter environmentally sensitive areas.
- Good rust and corrosion protection.
- Superb low-temperature capabilities and high viscosity index allow a wide operating temperature range.
- Increased resistance to varnish, carbon and acid formation, providing better protection and longer service life, especially during extreme and/or hot operating conditions.
- Excellent film strength resulting in exceptional equipment performance that not only results in fewer breakdowns but helps improve production capacity.
- Separates readily from water.
- Reduced energy consumption.
- High flash & auto ignition points
- Low pour point.
- Very low volatility, lower evaporation loss for good vacuum performance.
- Reduced maintenance with very long drain intervals.
- Excellent foam control, reducing heat, oxidation and wear. High contact regions are protected against wear for increased vacuum pump and compressor life and efficiency
- For vacuum applications down to 10-1 mbar



