

FOOD-PLUS ECO COMP 46

FOODGRADE & BIODEGRADABLE COMPRESSOR OILS

323301401



SYNTHETIC BIODEGRADABLE COMPRESSOR AND VACUUM PUMP LUBRICANT – FOOD GRADE

The product is formulated by combining top-quality synthetic base fluids with specially engineered additives. It has proven to be highly effective in equipment that operates under severe conditions and requires a food grade and/or environmentally friendly lubricant with this ISO viscosity grade. The product is specifically designed for use in the food and beverage industries where there is a possibility of incidental contact with lubricants. These lubricants are fully compatible with mineral oil-based oils and PAG's, making flushing generally unnecessary when switching to this product. However, it's important to note that biodegradability will be compromised if two different product types are mixed. Therefore, it's recommended to minimize any residual amounts of old lubricants. It's also crucial to use paint finishes with a 2-part epoxy system and avoid metals such as zinc and tin wherever possible. The cleaning properties of these fluids can dislodge significant amounts of dirt, which may shorten filter lifespan during changing periods. To prevent this,

it's recommended to keep the water content during use below 0.1%, and to drain any collected water.

PROPERTY	METHOD	VALUE
ISO Viscosity Grade	ASTM D2422	46
Viscosity @ 100 °C, mm ² /s	ASTM D445	7.9
Viscosity @ 40 °C, mm ² /s	ASTM D445	46
Viscosity index	ASTM D2270	140
Pour point, °C	ASTM D97	-39
Flash point C.O.C, °C	ASTM D92	260
Density @ 15 °C, kg/dm ³	ASTM D1298	0.97

CATEGORY

- Compressor- and Vacuum pump Fluids

BENEFITS

- Low toxicity
- Ready biodegradable (OECD 301B) and virtually non-toxic. These products are an excellent choice where leakage or spillage could enter environmentally sensitive areas
- Good rust and corrosion protection
- Superb low-temperature capabilities and high viscosity index allow a wide operating temperature range
- Increased resistance to varnish, carbon and acid formation, providing better protection and longer service life, especially during extreme and/or hot operating conditions
- Excellent film strength resulting in exceptional equipment performance that not only results in fewer breakdowns but helps improve production capacity
- Separates readily from water
- Reduced energy consumption
- High flash & auto ignition points
- Low pour point
- Very low volatility, lower evaporation loss for good vacuum performance
- Reduced maintenance with very long drain intervals
- Excellent foam control, reducing heat, oxidation and wear. High contact regions are protected against wear for increased vacuum pump and compressor life and efficiency
- For vacuum applications down to 10-1 mbar

All data on this technical data sheet is indicative only

202503V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE