
FOOD-PLUS GEAR GEN-T 680

FOODGRADE GEAR OILS



FOOD GRADE GEAR OIL

The product is a high-performance Food Grade Gear oil that combines the latest base stock technology with specially designed additives. All the base materials used in its formulation are food grade and non-toxic. It's important to note that this product is NSF HI registered for incidental food contact, ensuring its safety for use in food-related applications. With its exceptional performance characteristics and thoughtfully selected additives, this product is suitable for use in a wide range of applications throughout the food production and processing industry. Specifically, it has been developed for lubricating gears and gearboxes, conical and helical gears, bearings, chains, screws, joints, and other components that require a viscosity of ISO 68 or higher.

323500701

PROPERTY	METHOD	VALUE
Colour		Transparent
Density @ 20 °C, kg/dm³		0.870
Viscosity @ 40 °C, mm²/s		680
Viscosity index		120
Pour point, °C		<-12
Flash point C.O.C, °C		>250
Demulsibility (ASTM D1401, 40/37/3-30min)		Pass
4-ball wear test- Welding load, kg		
FZG value		12
NSF registration		151737
Kosher approved		Yes
Halal approved		Yes



All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

CATEGORY Gear Oils

BENEFITS

DYADE LUBRICANTS