
FOOD-PLUS GEAR PAG GEN 150

FOODGRADE GEAR OILS 323500901



DDODEDTV

SYNTHETIC GEAR AND CHAIN OIL FOR THE FOOD **INDUSTRY**

The product line comprises high-performance synthetic food grade gear oils that are ideal for lubricating gearboxes, reduction units, drive chains, and conveyor chains, providing long-lasting performance. These fluids are engineered to offer excellent anti-wear properties, high stability against oxidation, and a low pour point. They resist mechanical shearing and remain stable during aging, exhibiting favorable viscosity-temperature characteristics. The fluids are also adhesive, which effectively prevents wear during startup operations. Additionally, the product is NSF H1 registered, making it safe for incidental food contact. The primary purpose of this product is to lubricate gearboxes, bearings, endless screws, circulating systems, and conveyor chains (up to 240°C). It is particularly suitable for use in very humid environments as it remains impervious to water.

VALUE

PROPERTY	METHOD	VALUE	
Colour	Visual	Colorless	
Density @ 20 °C, kg/dm³	ASTM D1298	0.998	
Viscosity @ 40 °C, mm²/s	ASTM D445	162	
Viscosity @ 100 °C, mm²/s	ASTM D445	27	
Viscosity index	ASTM D2270	202	
Flash point, °C	ASTM D92	278	
Pour point, °C	ASTM D97	-39	
TAN, (max) mg KOH/g	ISO 6618	1.6	
Copper Corrosion	ASTM DI30	la	
4-ball Wear, 1200 rpm, 75°C, 40kg	ASTM D4172	0.35	
4-ball Weld load, kg	ASTM D2783	160	
Rust Test		Pass	
FZG load stage	DIN 51 354	>12	
NSF approval, H1		Pending	
Kosher approved		YES	
Halal approved		YES	

METHOD



CATEGORY

Gear Oils

BENEFITS

- Extremely good oxidation stability extending
- Excellent water resistant properties, demulsibility ensures total separation of water from oil
- Adhesive
- Penetrates to chain links and pins reducing wear and extending chain life
- Non-dripping
- Protects from corrosion even in presence of alkali
- Extremely wide temperature range
- Excellent resistance to high loads



