FOOD-PLUS GEAR PAO GEN 460

FOODGRADE GEAR OILS



SYNTHETIC AND FOOD GRADE GEAR OIL

This is a series of fully synthetic food grade gear oils that are ideal for lubricating drive chains, conveyor chains, gearboxes, and reduction units. They are formulated with special additives that prolong the re-lubrication intervals. Additionally, the product is NSF HI registered, making it safe for incidental food contact. This product is recommended for use in gearboxes, reduction units, drive, and conveyor chains. To achieve optimal performance, it is advised to drain the gearbox of any previously used lubricants.

PROPERTY	METHOD	VALUE	
Density kg/dm³	ASTM D1298	0.85	
Kin. viscosity @ 40°C, cSt	ASTM D445	460	
Kin. viscosity @ 100°C, cSt	ASTM D445	44	
Viscosity index	ASTM D2270	>160	
Flash point, °C	ASTM D92	>260	
Pour point, °C	ASTM D97	<-40	
FZG, stage	DIN 51 354	12+	
NSF registration		147086	
Kosher approved		YES	
Halal approved		YES	

CATEGORY

323502101

Gear Oils

BENEFITS

- Extremely good oxidation stability which extends lubricant life
- Unaffected by water demulsibility ensures total separation of water from oil
- Adhesive additives coat gears and provide antiwear protection at start-up
- Synthetic oil with HVI ensures reduced viscosity change with temperature increase
- Penetrates to links and pins reducing wear and extending chain life
- Adhesive additives ensure non-drip, no fling thus providing lasting lubrication
- Excellent adhesive characteristics ensures a high degree of water resistance and protects parts from corrosion even in the presence of alkali materials commonly associated with the food industry
- Extremely wide temperature range ensures maximum application versatility



All data on this technical data sheet is indicative only

202312V01



TYPOGRAAF 16 | 6921 VB DUIVEN

DYADE MAINTAIN THE THINGS WE VALUE