

FOOD-PLUS GREASE TRANSLUC 2

FOODGRADE GREASES

323701601



TRANSLUCENT FOOD GRADE GREASE

This product is a food-grade lubricating grease suitable for various applications, such as the lubrication of plain and rolling element bearings in food processing plants, slaughterhouses, canning and bottle factories. The gel-like grease, composed of non-melting and non-toxic ingredients, is highly appropriate for lubricating plastic components and O-rings.

CATEGORY

- Greases

BENEFITS

- Excellent performance in the presence of water
- Translucent which provides a clean operation
- Normal working temperatures: -20 +150 °C
- High intermediate temperatures possible (no dropping point)
- Very adhesive
- Good resistance to vibrating conditions extending lubrication intervals

PROPERTY	METHOD	VALUE
Appearance		White translucent
Thickener		Silica
Base oil type		White oil
Base oil viscosity @ 40 °C, mm ² /s		330
Penetration @ 25 °C	ASTM D217	290-310
NLGI class	DIN 51 818	2
Worked penetration @ 60W, x 0,1 mm	ASTM D217	265-295
Dropping point	IP 132	None
Water washout @ 38 °C, % max	ASTM D1264	< 2
4-ball wear test, welding load, kg	IP 239	210
dN factor		500.000
Operating temperatures, °C		-40 - 160
NSF registration		140112
Kosher approved		yes
Halal approved		yes

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE