## **FOOD-PLUS GREASE BENTO-WO 2**

FOODGRADE GREASES 323701901



## **INORGANIC GREASE FOR DIRECT FOOD CONTACT**

This non-toxic grease is formulated to perform across a wide range of temperatures and contains lubricityenhancing additives, including anti-wear agents. It is suitable for use with plain and anti-friction bearings, as well as sliding surfaces. This product serves as a release agent (category 3H) for hard surfaces that come into contact with meat and poultry during processing, such as grills, ovens, loaf pans, chopping boards, and boning benches. It prevents food from sticking and adhering during the process. Its primary application is for hand tools and cutters used in the meat processing industry, which are typically lubricated with an H-1 approved grease based on aluminium complex or inorganic thickeners. However, production dropouts can occur due to challenging circumstances. This product can significantly increase production output. It can also be used as a lubricant for slider bearings and roller bearings, with some limitations.

| PROPERTY                                       | METHOD     | VALUE     |
|--|------------|-----------|
| Appearance                                     | Visual     | White     |
| Thickener                                      |            | Inorganic |
| NLGI class                                     |            | 1.5       |
| Dropping point                                 | IP 132     | None      |
| Base oil                                       |            | White oil |
| Base oil viscosity @ 40 °C, mm²/s              |            | 100       |
| Base oil viscosity @ 100 °C, mm²/s             |            | 11.8      |
| Copper corrosion                               | IP 112     | Pass      |
| Water washout @ 38°C, %                        | ASTM D1264 | <2        |
| Dynamic corrosion resistance EMCOR             | IP 220     | 0:0       |
| 4 ball wear test - Welding load, kg            | IP 239     | 400       |
| 4 ball wear test - Scar dia. @ 40 °C, 1 hr, mm | IP 239     | 0.83      |
| FOUT   |            | 0.957     |
| Service temperatures, °C                       |            | -30 - 120 |
| NSF registration                               |            | 148466    |
| Kosher approved                                |            | Yes       |
| Halal approved                                 |            | Yes       |



## **CATEGORY**

Greases

## **BENEFITS**

- Provides long term lubrication at wide temperatures, extending lubrication intervals
- Will increase production output
- Good sealing properties protect against the ingress of corrosive contaminants
- Improved anti-wear performance prolonging component life



