FOOD-PLUS HYDRAU HLP 46

FOODGRADE HYDRAULIC OILS







RANGE OF MULTIPURPOSE LUBRICATING OILS FOR THE FOOD INDUSTRY The formulation of this product comprises of

meticulously chosen additive technology and highly refined base stocks. It is a non-toxic solution that can be used in applications where the possibility of incidental contact with food or raw materials during production is high. The product's excellent performance characteristics and selected additives make it suitable for use in most manufacturing processes in the food production and processing industry. It is available in a wide range and holds NSF approval.

PROPERTY	METHOD	VALUE
Density @ 20 °C, kg/dm³		0.850
Viscosity @ 40 °C, mm²/s		46
Viscosity index		105
Pour point, °C		-18
Flash point C.O.C, °C		210
Acidity index, mg KOH/gr		0.8
Aniline point, °C		105
Copper corrosion 3h @ 100 °C		la
Rust test A (distilled water)		Pass
De-emulsifying index		40/37/3 (30')
NSF registration		138238
Kosher approved		Yes
Halal approved		Yes

CATEGORY

Hydraulic Fluids

BENEFITS

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V. TYPOGRAAF 16 | 6921 VB DUIVEN THE NETHERLANDS

DYADE MAINTAIN THE THINGS WE VALUE