FOOD-PLUS HYDRAU HLP 68

FOODGRADE HYDRAULIC OILS







RANGE OF MULTIPURPOSE LUBRICATING OILS FOR THE FOOD INDUSTRY

The formulation of this product comprises of meticulously chosen additive technology and highly refined base stocks. It is a non-toxic solution that can be used in applications where the possibility of incidental contact with food or raw materials during production is high. The product's excellent performance characteristics and selected additives make it suitable for use in most manufacturing processes in the food production and processing industry. It is available in a wide range and holds NSF approval.

| PROPERTY | METHOD | VALUE |
|-------------------------------|--------|---------------|
| Density @ 20 °C, kg/dm³ | | 0.860 |
| Viscosity @ 40 °C, mm²/s | | 68 |
| Viscosity index | | 105 |
| Pour point, °C | | -15 |
| Flash point C.O.C, °C | | 210 |
| Acidity index, mg KOH/gr | | 0.8 |
| Aniline point, °C | | 105 |
| Copper corrosion 3h @ 100 °C | | la |
| Rust test A (distilled water) | | Pass |
| De-emulsifying index | | 40/37/3 (30') |
| NSF registration | | 138237 |
| Kosher approved | | Yes |
| Halal approved | | Yes |



Hydraulic Fluids

BENEFITS

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V. TYPOGRAAF 16 | 6921 VB DUIVEN THE NETHERLANDS *𝔅* ^𝔅
 <sup>𝔅
 ^𝔅
 <sup>𝔅
 </sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup></sup>