

# GREASE-PLUS LI-SYNT LT 3

GREASES

324902101

**DYADE**  
LUBRICANTS



## SPECIAL GREASE FOR THE LUBRICATION OF ELECTRICAL CONTACTS

This product is composed of synthetic oils with high chemical and temperature stability. It is designed to create a thin and stable lubricating film on contact surfaces in switches and electrical mechanisms. This film improves the circulation of electric power and prolongs the lifespan of metallic contact surfaces. In addition, the product provides excellent anticorrosive protection that prevents the interruption of electric power circulation caused by salts or surface oxides. It also prevents the wear of corroded metal contact surfaces.

## CATEGORY

- Greases

## BENEFITS

- Contact improvement of metallic contact surfaces and superior distribution and circulation of electric power
- Wear and breakage reduction
- Longer life of the mechanisms
- Secures a quick response after long stoppage periods
- No build-up of non-conductive salts or rust

PROPERTY	METHOD	VALUE
Colour		Beige
Thickener		Lithium
Base oil type		Synthetic
Base oil viscosity @ 40 °C, mm <sup>2</sup> /s		12
NLGI class		3
Penetration @ 25 °C, x 0,1 mm		220-250
Dropping point, °C		180
Oil separation, 18h/40 °C, %		0,50
Worked penetration 105W, mm		305
Flow pressure @ -40 °C, mbar		700
Water resistance, 3h/90 °C		1
Oil separation 7d/40 °C, %		1,80
Oxidation stability, 100h/100 °C, kg/cm <sup>2</sup>		0,70
Evaporation loss, weight, 22hr/100 °C, %		2
Service temperatures, °C		-65 - 130

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM