

GREASE-PLUS BENTO-MO HT 2

GREASES

324902901



INORGANIC GREASE FOR BEARINGS

Crafted for high-demand lubrication applications, this product is a superior quality inorganic clay grease. It boasts a non-melting formula and is made from high-viscosity index base oils to ensure optimal performance. This product is specifically designed for use in medium and low-speed applications that involve severe operating conditions, making it a superior alternative to standard greases. It is suitable for lubricating bearings, hinges, chains, and pins.

CATEGORY

- Greases

BENEFITS

- Resistant to high temperatures
- Operating temperatures from -30 to 180 °C
- Does not drop
- Resists mechanic working
- Excellent thermal stability
- Oxidation resistance
- Long life grease

PROPERTY	METHOD	VALUE
Colour	Visual	Brown
Thickener		Inorganic
Base oil viscosity @ 40 °C, mm ² /s	ASTM D7152	460
NLGI grade	ASTM D217	2
Penetration @ 60W, x 0,1 mm	ISO 2137	265-295
Dropping point	IP 396	None
Service temperature, °C		-30 - 180

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE