

# GREASE-PLUS BENTO-MO MT 2

GREASES

324903001

**DYADE**  
LUBRICANTS



## INORGANIC GREASE FOR BEARINGS

Formulated with an inorganic thickener and mineral oil, this high-performance non-melting grease is specifically designed to lubricate equipment that operates at high temperatures. This grease is designed for use in medium-speed, high-temperature bearings where standard EP greases are likely to fail due to their inability to withstand high temperatures.

## CATEGORY

- Greases

## BENEFITS

- Resistant to high temperatures
- Operating temperatures from -30 to 180 °C
- Does not drop
- Resists mechanic working
- Excellent thermal stability
- Oxidation resistance
- Long life grease

PROPERTY	METHOD	VALUE
Colour	Visual	Brown
Thickener		Inorganic
Base oil nature		Mineral
Base oil viscosity @ 40 °C, mm <sup>2</sup> /s	ASTM D445	160
NLGI grade	ASTM D217	2
Penetration @ 60W, x 0,1 mm	ISO 2137	265-295
Dropping point	ASTM D2265	None
Service temperature, °C		-30 - 180

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM