

# GREASE-PLUS LI-MO HD 00

GREASES

324905201

**DYADE**  
LUBRICANTS



## FLUID GEAR GREASE

This grease is specially formulated with an exceptional additive package and does not contain solid lubricants. It possesses a high load capacity and provides exceptional protection against wear and corrosion. Additionally, it exhibits good water resistance properties. This product is appropriate for lubricating rams in mechanical presses, gear motors, small and worm gears that contain steel or steel components, toothed couplings, slide ways, guides, and large chain drives. It can be used with centralized systems or for immersion lubrication of gears. Additionally, it has been specially formulated to provide high load capacity and superior protection against wear and corrosion, and to exhibit good water resistance properties.

## CATEGORY

- Greases

## BENEFITS

- Excellent anti wear and EP properties
- Good anti corrosion behaviour
- Good pumpability
- Fluid grease of excellent capacity of recirculation

PROPERTY	METHOD	VALUE
Colour		Dark amber
Thickener		Lithium
Base oil		Mineral
Base oil viscosity @ 40 °C, mm <sup>2</sup> /s		680
Unworked penetration @ 25 °C, 0,1 mm		430-465
NLGI class		00/000
4-ball wear test, welding load, kg		>700
FZG stage, conditions: A/2.76/50		>12
Service temperatures, °C		-10 - 100

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM