

GREASE-PLUS LI-SIL 2

GREASES

324907201

DYADE
LUBRICANTS



SILICON GREASE FOR LOW OPERATING TEMPERATURES

These are greases formulated with a lithium soap thickener and a methyl-phenyl-silicone base oil for use in low operating temperatures.

CATEGORY

Greases

BENEFITS

PROPERTY	METHOD	VALUE
Colour		White ivory
Thickener, soap type		Lithium
Base oil type		Methyl-phenyl silicone oil
Base oil viscosity @ 25 °C, mm ² /s		10.000
Penetration @ 25 °C	ASTM D217	265-295
Drop point, °C	ASTM D566	> 200
NLGI class	DIN 51 818	2
Water resistance	DIN 51 807	1
EMCOR corrosion test	DIN 51 802	1
Flow pressure @ -35 °C, mbar	DIN 51 805	300
Evaporation loss, 48hr/150 °C, %	ASTM D972	1,5
Oil separation 7 days/40 °C, %	IP 121	6
Service temperature, °C		-73 - 180

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM