

# GREASE-PLUS LI-MO PTFE 2

GREASES

324907301

**DYADE**  
LUBRICANTS



## LITHIUM GREASE WITH PTFE

This multipurpose grease is of premium quality and offers exceptional performance and protection in a variety of applications. It has the ability to penetrate and create long-lasting protection that can endure heavy loads and high temperatures. This versatile lubricating grease is ideal for all metal-to-metal lubrication and is highly recommended for use in various industrial, workshop, DIY, and marine applications. It provides long-lasting protection against heavy loads and high temperatures. It is the perfect all-round grease for ball, roller, and needle bearings, as well as for machinery tools, fan motors, slides, gears, cables, couplings, hitches, and winches.

## CATEGORY

- Greases

## BENEFITS

- Outstanding mechanical and aging stability
- Working temperature from -30 up to 120 °C
- Good water washout properties

PROPERTY	METHOD	VALUE
Colour		Beige
Thickener		Lithium
Base oil type		Mineral
Base oil viscosity @ 40 °C, mm <sup>2</sup> /s		100
NLGI class	DIN 51 818	2
Drop point, °C		180
Worked penetration, 60W, x 0,1 mm	ASTM D217	265-295
Mechanical stability roller test, x 0,1 mm	ASTM D1831	+45
4-ball wear test, welding load, kg	IP 239	400
Water washout @ 80 °C	ASTM D1264	4
Water resistance 3h/90 °C	DIN 51 807	1
Storage oil separation (%) - @ 18h/40 °C	DIN 51 817	1.5
Storage oil separation (%) - @ 7h/40 °C	DIN 51 817	5.0
EMCOR corrosion test	DIN 51 802	1/0
Copper corrosion 24h @ 100 °C	ASTM D4048	1b
PTFE content, %		6
Working temperature, °C		-30 - 120

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM