

PASTE-PLUS 225

PASTES

325000501



HIGH PERFORMANCE HIGH TEMPERATURE ANTI SEIZE PASTE FORTIFIED WITH CERAMIC COMPONENTS

The non-melting high temperature soft grease-like compound in this product is of premium quality and contains an exceptionally high concentration of non-metallic solids. It is ideal for use during assembly and running-in procedures. The purpose of this compound is to safeguard against corrosion and damage during the assembly process, as well as provide protection against premature wear during the running-in period.

CATEGORY

- Pastes

BENEFITS

- Low friction coefficient provides excellent protection during running-in, prolonging component life
- Protection under high load reduces component wear
- Provides protection against scuffing during the assembly of interference fits, saving on assembly time
- Prevents seizure of threaded components enabling easy and quick dismantling
- Dismantled threaded components can be re-used

PROPERTY	METHOD	VALUE
Colour		White smooth paste
Thickener		Inorganically modified clay
NLGI consistency		2
Dropping point, °C		>260
Lubricating solids		White non-metallic solids
Copper corrosion	IP 112	1b
Aluminium corrosion	IP 112	Negative
Mild steel corrosion	IP 112	Negative

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM