

# RP-PLUS DEW 35

RUST PREVENTATIVES

325200201

**DYADE**  
LUBRICANTS



## DEWATERING RUST PREVENTION FLUID

Containing solvents, rust inhibitors, and hydrophobic additives, this product is a fluid that displaces moisture and water from parts. It leaves behind a greasy-oily film that offers excellent anti-rust properties. Typically, it is applied to parts that require protection and have been machined with soluble oils. Additionally, it is suitable for safeguarding parts that have been quenched with water before being packed or for protecting machinery parts exposed to corrosive moisture.

## CATEGORY

■ Rust Preventatives

## BENEFITS

PROPERTY	METHOD	VALUE
Nature		Liquid with solvents
Application		At room temperature
Density @ 20 °C, kg/dm <sup>3</sup>		0.79
Drying time, minutes		30
Chemical reaction		None
Flash point C.O.C, °C		40
Indoor protection, months		< 18
Removal/cleaning detergents		By solvents or alkaline

All data on this technical data sheet is indicative only

202312V01



**DYADE** MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADEGLOBAL.COM  
WWW.DYADEGLOBAL.COM