

RP-PLUS OB 67

RUST PREVENTATIVES

325200801



OILY FILM ANTICORROSIVE AGENT

Designed to provide excellent protection against rust, this product is a high-quality, oil-based rust preventive that forms a thin, oily film on both ferrous and non-ferrous metals. It is specifically formulated for indoor storage applications where long-term protection is needed, typically ranging from 6 to 12 months. Typical applications include: Protection of finished machine components prior to packaging Steel sheets, profiles and rolled strips Industrial motors Car and truck engines Inter-operational protection of finished machined or ground metal surfaces such as valves, rollers and fasteners Protection of parts during storage where a thin oily film is required

CATEGORY

- Rust Preventatives

BENEFITS

- High anticorrosive capacity
- Compatibility with lubricating oils
- Easy removal
- High coating capacity
- Free of barium and solvents

PROPERTY	METHOD	VALUE
Appearance		Light brown
Density @ 20 °C, kg/dm ³		0.88
Viscosity @ 40 °C, mm ² /s		12-15
Flash point C.O.C, °C		<130
Indoor protection (months)		6-12

All data on this technical data sheet is indicative only

202312V01



DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM

DYADE MAINTAIN THE THINGS WE VALUE