

RP-PLUS OB 72

RUST PREVENTATIVES

325201101



OIL BASED RUST PREVENTATIVE

Designed for storage lasting between three to six months, this high-quality rust preventive product is oil-based and free of barium. It forms an oily film that provides long-term protection to both ferrous and non-ferrous metals. Additionally, the product's thixotropic properties ensure optimal film stability on all types of surfaces. Typical applications include: Protection of finished machine components prior to packaging Steel sheets, profiles and rolled strips Industrial engines Car and truck engines Inter-operational protection of finished machined or ground metal surfaces such as valves, rollers and fasteners Protection of parts during storage where a thin oily film is required

CATEGORY

■ Rust Preventatives

BENEFITS

PROPERTY	METHOD	VALUE
Appearance		Light brown
Density @ 20 °C, kg/dm ³		0.88
Viscosity @ 40 °C, mm ² /s		25-29
Flash point C.O.C, °C		180
Salt spray test, hours		24
Storage (months)		3-6

All data on this technical data sheet is indicative only

202312V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADEGLOBAL.COM
WWW.DYADEGLOBAL.COM